



Smart Network Access System

1U Modular Chassis



- ⚡ Four (4) Hot-swappable module slots
- ⚡ One (1) Expansion Slots
- ⚡ 20 Gigabit Aggregating and Routing backplane
- ⚡ Dual AC or DC - 48vdc power supplies
- ⚡ Local or remote configuration available
- ⚡ Modular design provides the ability to make updating your infrastructure quick, easy and inexpensive.
- ⚡ Easily installs anywhere in the network infrastructure.
- ⚡ Supports Copper and Fiber Environments
- ⚡ Allows secure and easy access for all of your network appliances
- ⚡ High density design saves rack space and power consumption
- ⚡ Reduces number of power outlet and UPS connections needed
- ⚡ Eliminates power cord management
- ⚡ Helps achieve green data center status
- ⚡ Chassis weight is 40% less than previous models

Product Specifications

Size Dimensions (W x H x D)	44.05 cm x 4.4 cm x 31.63 cm/ 17.33 in x 1.73 in x 12.44 in
Weight	7.0 lbs/ 3.2 kg
Operating Temperature	0°C to +40°C / +32°F to +104°F
Operating Relative Humidity	90 % non-condensing
Storage Temperature	-20°C to +70°C/ -4°F to +158°F
Voltage (AC/DC)	85V–264V AC/36V–72V DC
Current (nominal)	0.22 A @ 230 VAC/0.44A @ 110VAC/ 1.5 A @ 50 VDL
Frequency	47–63 Hz
Power Consumption	50 Watts

Ordering Information:

SNAC1AC— 1U Modular Chassis, 4 Hot Swappable Slots, 1 Expansion Slot, Dual AC Power Supplies

SNAC1DC— 1U Modular Chassis, 4 Hot-Swappable Slots, 1 Expansion Slot, Dual DC-48vdc Power Supplies

Headquarters

12B Southview Park
Caversham, Reading, RG4 5AF
0118 954 3210
Sales@NetworkCritical.com

WWW.NETWORKCRITICAL.COM

Americas Office

3675 Harlem Road
Buffalo, NY 14215
(716) 558-7280
Sales-US@NetworkCritical.com