



# Smart Network Access System

## 2U Modular Chassis



- ⚡ Twelve (12) Hot-swappable module slots
- ⚡ Three (3) Expansion Slots
- ⚡ Dual AC or DC - 48vdc power supplies
- ⚡ Local or remote configuration available
- ⚡ Modular design provides the ability to make updating your infrastructure quick, easy and inexpensive.
- ⚡ Easily installs anywhere in the network infrastructure.
- ⚡ Supports Copper and Fiber Environments
- ⚡ Allows secure and easy access for all of your network appliances
- ⚡ High density design saves rack space and power consumption
- ⚡ Reduces number of power outlet and UPS connections needed
- ⚡ Eliminates power cord management
- ⚡ Helps achieve green data center status
- ⚡ Chassis weight is 40% less than previous models

### Product Specifications

Size Dimensions (W x H x D)	17.33 in x 3.46 in x 12.44 in/ 44.02 cm x 8.80 cm x 31.60 cm
Weight	8.7 lbs/3.9 kg
Operating Temperature	0°C to +40°C / +32°F to +104°F
Operating Relative Humidity	90 % non-condensing
Storage Temperature	-20°C to +70°C/ -4°F to +158°F
Voltage (AC/DC)	85V–264V AC/36V–72V DC
Current (nominal)	6A @ 115 VAC/3A @ 230VAC/ 1.5 A @ 50 VDL
Frequency	47–63 Hz
Power Consumption	50 Watts

### Ordering Information:

SNAC2AC— 2U Modular Chassis, 12 Hot Swappable Slots,3 Expansion Slot, Dual AC Power Supplies

SNAC2DC— 2U Modular Chassis, 12 Hot-Swappable Slots,3 Expansion Slot, Ducaal DC-48vdc Power Supplies

#### Headquarters

12B Southview Park  
Caversham, Reading, RG4 5AF  
0118 954 3210  
Sales@NetworkCritical.com

**WWW.NETWORKCRITICAL.COM**

#### Americas Office

3675 Harlem Road  
Buffalo, NY 14215  
(716) 558-7280  
Sales-US@NetworkCritical.com